

## 400-1228 / 401-1228

### Mini NEOBE® Power Supply



**World's Smallest  
NEOBE® Power Supply!**

#### 400-1228 / 401-1228 MINI NEOBE® POWER SUPPLY

The model 400 is a low cost remote NEOBE® power supply designed to alternately flash any two remote strobe heads at a rate of 60 flash bursts per minute each. The unit is a tiny 2" x 3" x 1.5" for easy mounting in any area. The 400 is fully potted making it vibration and water resistant. The unit features polarity protection, continuous duty circuitry, and RFI filters to protect against radio interference. The 400 operates on 12 thru 28VDC and is fully protected against shorts or opens in the lamp wiring.

#### Power Requirements:

Draws 1.85 A avg. @12VDC tapering to 0.9 A avg. @24VDC

#### Output Power Rating:

20 Watts minimum

#### Flash Rate:

60 Bursts/MIN/Head  
6 Flashes/Burst

#### Construction:

ABS case, polyurethane potting

#### Size:

2" (50.8mm) x 3" (76.2mm) x 1.5" (38.1mm)

#### Weight:

0.6 lbs (276 grams)

#### Mounting Hole Dimensions:

2 Holes, 0.187" Dia (4.75mm)

#### Ordering Information

Model No.	Description
400-1228	2 output NEOBE® power supply
400-1228-WP	(Same as above except with Waterproof connectors)
401-1228	1 output NEOBE® power supply
401-1228-WP	(Same as above except with Waterproof connectors)
401-CF-1228	1 output continuous flash power supply
401-CF-1228-WP	(Same as above except with Waterproof connectors)

