

Cable Kits

Cables for Lamps and Power Supplies

TOMAR multi-conductor lamp extension cables are available in eight styles to allow connecting standard lamps and power supplies to WP lamps and power supplies. STD connectors are recommended for use in clean/dry areas only; they are not water tight or weatherproof. WP connectors are recommended for use in damp/wet areas and are sealed with silicone rubber gaskets, and are rated for automotive under hood applications. The cable is shielded 3/C-16AWG 26/30 stranding annealed tinned copper color coded PVC insulated and jacketed and rated for 80°C operation. .274" O.D.



STD. FEMALE
M43A/M37A



STD. MALE
M44A/M38A



WP. MALE
M1054/M1056



WP. FEMALE
M1053/M1055

Ordering Information

Model No.	Cable Length	Cable Type	Connector (Power Supply End)	Connector (Lamp End)
0.5C 2C 6C 9C 15C 20C 25C	6 inches 2 feet 6 feet 9 feet 15 feet 20 feet 25 feet	C	Standard Female	Standard Male
0.5C-WP 2C-WP 6C-WP 9C-WP 15C-WP 20C-WP	6 inches 2 feet 6 feet 9 feet 15 feet 20 feet	C	WP Male	Standard Male
0.5C-WP1 6C-WP1 9C-WP1 15C-WP1 20C-WP1	6 inches 6 feet 9 feet 15 feet 20 feet	C-WP	Standard Female	WP Female
2C-WP2 6C-WP2 9C-WP2 15C-WP2 20C-WP2	2 feet 6 feet 9 feet 15 feet 20 feet	C-WP	WP Male	WP Female

Model No.	Cable Length	Cable Type	Connector (Power Supply End)	Connector (Lamp End)
2-2LH 4-2LH 15-2LH 20-2LH 35-2LH	2 feet 4 feet 15 feet 20 feet 35 feet	2LH	Standard Female	Standard Male
2-2LH-WP 4-2LH-WP 15-2LH-WP 20-2LH-WP 35-2LH-WP	2 feet 4 feet 15 feet 20 feet 35 feet	2LH-WP	WP Male	Standard Male
2-2LH-WP1 4-2LH-WP1 15-2LH-WP1 20-2LH-WP1 35-2LH-WP1	2 feet 4 feet 15 feet 20 feet 35 feet	2LH-WP1	Standard Female	WP Female
2-2LH-WP2 4-2LH-WP2 15-2LH-WP2 20-2LH-WP2 35-2LH-WP2	2 feet 4 feet 15 feet 20 feet 35 feet	2LH-WP2	WP Male	WP Female

*Special lengths can be made to order.